

SUPRA NATURAL RUBBER CUTTING HOSE

Natural Rubber welding and cutting hoses are designed to safely convey gases such as oxygen, acetylene, and LPG used in welding, brazing, and cutting operations. These hoses are made from high-quality natural rubber, ensuring flexibility, strength, and excellent resistance to wear, oil, and flame exposure.

SALIENT FEATURE

- Conforms to IS: 447 for welding and cutting hoses.
- Oil, flame & abrasion resistant outer cover.
- Rigorously tested for pressure leakage and adhesion strength.
- Meets industrial safety norms for gas welding & cutting applications.

Uses

- Gas welding & cutting operations
- Brazing and heating processes
- Metal fabrication & maintenance workshops
- Automotive repair, shipbuilding & heavy engineering industries



TECHNICAL SPECIFICATIONS

Parameter	: Specification
Material	: Natural Rubber Compound
Reinforcement	: High-tensile Synthetic Yarn
Working Pressure	: 20 Bar
Burst Pressure	: 60 Bar
Temperature Range	: -20°C to +70°C
Color Coding	: Red – Acetylene / Blue – Oxygen / Orange – LPG
Inner Diameter (mm)	: 8x15 mm
Length	: Standard 100 meters (Roll)

MATERIAL CODE	DESCRIPTION	HSN CODE	PACKING DETAILS
TRG0001080	SUPRA NATURAL CUTTING HOSE RED	40093100	100 MTR
TRG0001090	SUPRA NATURAL CUTTING HOSE BLUE	40093100	100 MTR